

Anglebrace Rebater

TIMBER WALL FRAME REBATER

The Anglebrace Rebater is recommended for the rebating of timber on wall frames to accommodate MiTek® bracing.



The Anglebrace Rebater consists of a modified electric circular saw mounted on a 4.3 metre long beam with a handle at each end. Operation is easy. Simply place the top of the beam on top of the finished wallframe and push the saw along the beam.

As the saw crosses a stud it rebates the timber to the depth required. This depth is adjustable to allow for different types and gauges of bracing and for wear of the saw blades. The result is a straight and neatly finished rebate. For standard lengths of Anglebrace, the beam can be marked and positioned in such a way that the entire length of the bracing is used. This saves trimming and costly production time.

FEATURES

- Simple operation.
- Adjustable depth to allow for different types and gauges of bracing.
- Minimal maintenance - replace blade or re-tip Dado Cutters as required.
- Safe - blade guarded when not in cut.
- Nylon slide blocks and bearings for easy movement along beam.
- Lifting handles provided for easy movement of beam.
- Set-up time - few seconds, simply lay the beam across the wall frame and push the saw along the beam.

SPECIFICATIONS

Number of blades	1
Saw blade diameter	150mm
Dado Cutter (trenching blade) diameter	118mm for Minibrace or 114mm for Maxibrace
Length of travel (beam)	4.3m
Power requirements - standard 3-pin GPO power outlet	1-phase, 240VAC, 10A
Saw motor	1.05kW

OPTIONS

- Available with or without beam.
- Available to suit either of the following bracing types: Minibrace and Maxibrace.